

E35m

Instrumentation/Controls

The Bucher E35m Mechanical Sweeper features a central cab mounted control panel with warning and information LEDs for;

- Low Hydraulic Oil
- Conveyor Stall Alarm
- Hydraulic Oil Temperature
- Hydraulic Oil Filter Restriction Indicator
- Low Water Alarm
- Hopper Up Alarm

All wiring is colour coded and numbered. All internal and external wiring conforms to IP65 and IP67 standards - waterproof and dustproof.

Powertrain

Utilising an Allison 3500RDS automatic transmission, a 10,000lb front axle and a 23,000 lb two speed rear axle the E35m sweeper and chassis are matched for optimal travel speed, sweep speed and payload performance.

Brushes

Gutter broom	44" (1100 mm)
Main broom	34.5" x 58" (870 x 1470 mm)
Drives	Direct coupled hydraulic motor
Sweep path MB & (2) SB	120" (3050 mm)
Conveyor Type	Squeegee, 12 Flights
Sweeping speeds	2-15 mph

Gutter Broom

Large 44 inch, hydraulic driven, leading arm, digger type, free floating Gutter Broom with in-cab adjustable speed and down pressure insure aggressive cleaning of curbs and gutters

Option for the dual brooms to extend out to achieve a 144 inch total reach to facilitate cul-de-sac and curve sweeping.

Main Broom

Aggressive 34.5 x 58 inch polypropylene tube main broom is direct hydraulically driven and attached to two fully floating trailing arms to allow for changing road surfaces.

Dirt Shoes

The sweeper can be fitted with standard T-Plate steel skid dirt shoes with carbide inserts or new maintenance free stripbrush type dirt shoes.

Conveyor/Elevator

Chain driven, 12 flight- squeegee type conveyor over polyurethane sprockets. The conveyor height can be adjusted from in-cab to accommodate different sweeping requirements. The conveyor bearings are sealed and self-aligning.

Hopper

Variable Dump Height Hopper is raised and lowered via a heavy duty; two stage scissors lift with hydraulic cylinders.

Hopper voided volume ** 4.6 yd³ (3.4 m³)

Discharge angle 50° nominal

Door opening angle 90° nominal

Fabricated from heavy duty stainless steel plate.

Inspection hatch accessible from outside.

All lift and dump controls are hydraulic and located in-cab. Lift capacity is rated at 12,000lb and hopper dump angle is 50 degrees for efficient off-loading of debris.

Hydraulic System

20 gallon hydraulic reservoir supplying oil to a variable displacement hydraulic pump in a load sensing hydraulic system.

All hydraulic valves are equipped with light emitting diodes to signal function and feature manual overrides. All hydraulics are centrally located in their own system locker for ease of access and maintenance.

Water System

A 360 gallon baffled, polyethylene water tank provides the necessary water to supply a run-dry centrifugal pump delivering water to multiple water spray nozzles, strategically located at each gutter broom and over the main broom.

Water capacity 360 gallons (1400 l)

A range of options are available – contact us for more information.

Subject to change without notice.

** All Bucher Municipal Hopper Capacities are measured in accordance with European Standard EN 15429.

Votre partenaire contractuel Bucher Municipal :

PIÈCES D'ÉQUIPEMENT BERGOR INC.
Bureau administratif, équipements et pièces
48 Rue Jean-Marc-Séguin, Rigaud, Québec, J0P 1P0

T. 450-424-0801 SANS FRAIS 1-800-363-8218
F. Pièces 450-451-4188 F. Administration 450-451-6725

Web: www.bergor.ca - Courriel: info@bergor.ca

Bucher Municipal

For local contact
and support visit
www.buchermunicipal.com

Driven by better

